







	N°	Product Ref.	Material equivalent		Finish		QTY.	
	1	BF-11-55-LL-B	ZG45	Hot	1			
	2	BF-11-55-LL-C	C45	Hot dip galvanized			1	
	3	BF-Ball	Gcr15			1		
	4	BF-Spring	65Mn				1	
	First dra	wing	16/02/2021	MDH	BVQ	AC		
v.	Descript	tion of issue	Drawn by	Checked by	Approved by			
bdı	uct ref	Status: A	APPROVED					
e: U-FRAME TWISTLOCK LINE LOAD								
	nationa	II Lashing Systems	Website	Phone: +32-3-234.28.80 Website: www.ils.be E-mail: info@ils.be				

\searrow				N°	Product Ref.	Material equivalent	Finish			QTY.		
\bigwedge				1	BF-11-55-LL-B	ZG45	Hot	dip galva	anized	1		
$\langle \ \rangle$				2	BF-11-55-LL-C	C45	Hot	dip galva	anized	1		
\searrow						3	BF-Ball	Gcr15				1
~						4	BF-Spring	65Mn				1
Specifications:	Loads:		Shear	Tension	2							
Total weight: 7.4 kg	Breaking load	BL	420 kN	500 kN	1	First drawing			16/02/2021	MDH	BVQ	AC
RKING: ILS + PRODUCT CODE	Proof load	PL	263 kN	313 kN	Rev.	Descrip	tion of issue		Date	Drawn by	Checked by	Approved b
BATCH NUMBER	Safe working load	SWL	210 kN	250 kN	Product ref.: BF-11-55-LL Status:						Status: A	PPROVED
MM: MONTH OF PRODUCTION YY: YEAR OF PRODUCTION					Title: (U-FRAN	IE TWISTLOCK LINE	LOAD				e: 1:2 at: A3
Ownerschip of International Lashing Systems n.v. Duplication or disclosure to third parties in any form whatsoever, is prohibited without written permission of the owner.					ILS Phone: +32-3-234.28.80 International Lashing Systems Website: www.ils.be How secure is your cargo? E-mail: info@ils.be							

